

Bearing No.	Boundary dimensions(mm)				Basic load ratings(kN)		Limiting speed (rpm)		Weight
	尺寸				额定负荷		极限转速		重量
轴承尺寸	d	D	B	r _{smin}	Dynamic Cr	Static Cor	Grease	Oil	kg
					动态	静态	脂	油	
2200	10	30	14	0.6	7.3	1.59	19,000	23,000	0.047
2201	12	32	14	0.6	7.6	1.73	17,000	20,000	0.051
2202	15	35	14	0.6	7.7	1.85	15,000	18,000	0.06
2203	17	40	16	0.6	9.8	2.41	13,000	16,000	0.088
2204	20	47	18	1	12.6	3.3	12,000	14,000	0.14
2204K	20	47	18	1	12.6	3.3	12,000	14,000	0.137
2205	25	52	18	1	12.3	3.45	10,000	12,000	0.157
2205K	25	52	18	1	12.3	3.45	10,000	12,000	0.153
2206	30	62	20	1	15.2	4.5	8,600	10,000	0.256
2206K	30	62	20	1	15.2	4.5	8,600	10,000	0.25
2207	35	72	23	1.1	21.5	6.6	7,500	8,800	0.392
2207K	35	72	23	1.1	21.5	6.6	7,500	8,800	0.382
2208	40	80	23	1.1	22.3	7.35	6,700	7,900	0.493
2208K	40	80	23	1.1	22.3	7.35	6,700	7,900	0.482
2209	45	85	23	1.1	23.2	8.15	6,000	7,100	0.54
2209K	45	85	23	1.1	23.2	8.15	6,000	7,100	0.528
2210	50	90	23	1.1	23.2	8.45	5,500	6,400	0.583
2210K	50	90	23	1.1	23.2	8.45	5,500	6,400	0.569
2211	55	100	25	1.5	26.5	9.9	5,000	5,800	0.787
2211K	55	100	25	1.5	26.5	9.9	5,000	5,800	0.769
2212	60	110	28	1.5	34	12.6	4,600	5,400	1.08
2212K	60	110	28	1.5	34	12.6	4,600	5,400	1.06
2213	65	120	31	1.5	43.5	16.4	4,200	5,000	1.44
2213K	65	120	31	1.5	43.5	16.4	4,200	5,000	1.41
2214	70	125	31	1.5	44	17.1	3,900	4,600	1.52
2215	75	130	31	1.5	44.5	17.8	3,700	4,300	1.58
2215K	75	130	31	1.5	44.5	17.8	3,700	4,300	1.54
2216	80	140	33	2	48.5	19.9	3,400	4,000	1.99
2216K	80	140	33	2	48.5	19.9	3,400	4,000	1.95
2217	85	150	36	2	58	23.6	3,200	3,800	2.54
2217K	85	150	36	2	58	23.6	3,200	3,800	2.49
2218	90	160	40	2	70	28.7	3,100	3,600	3.19
2218K	90	160	40	2	70	28.7	3,100	3,600	3.12
2219	95	170	43	2.1	83.5	34.5	2,900	3,400	3.89

2219K	95	170	43	2.1	83.5	34.5	2,900	3,400	3.8
2220	100	180	46	2.1	94	38.5	2,700	3,200	4.65
2220K	100	180	46	2.1	94	38.5	2,700	3,200	4.54
2221	105	190	50	2.1	109	45	2,600	3,100	6.07
2222	110	200	53	2.1	124	51.5	2,500	2,900	7.1
2222K	110	200	53	2.1	124	51.5	2,500	2,900	6.94